

DC-18.0 GHz

FIXED PRECISION COAXIAL ATTENUATORS

- Extremely Low Frequency Sensitivity
- Very Low VSWR
- Environmental Performance Per MIL-A-3933E
- 2 Watt Rating
- Minimum Phase Response and Group Delay
- 7mm Connectors Versions and Precision Type N Connector Models



SPECIFICATIONS

7 mm*

FREQUENCY RANGE (GHz)	MODEL	ATTENUATION dB			POWER INPUT		VSWR (Max)			WEIGHT (Max)	
		NOMINAL	DEVIATION		AVG. (W) Max	PEAK (kW)Max	DC-4	4-12.4	12.4-18 GHz	Oz	Gr
DC-18	5779	3	±0.3	±0.3	2	0.2	1.10	1.25	1.35	3.5	99
		6	±0.3	±0.3	2	0.2	1.10	1.25	1.35	3.5	99
		10	±0.3	±0.5	2	0.2	1.10	1.25	1.35	3.5	99
		20	±0.5	±0.7	2	0.2	1.10	1.25	1.35	3.5	99
		30	±1.0	±1.25	2	0.2	1.10	1.25	1.35	3.5	99

* Non-standard attenuation values available upon special request. Minimum order quantity may apply. Consult factory for details